

# **MOBICON**

**Electronic Components**

## **PRODUCT SPECIFICATION**

### **MEC QUARTZ CRYSTAL**

### **FREQUENCY COMPONENTS**

**HC49S Series QUARTZ CRYSTAL SPECIFICATION**

<b>MOBICON HOLDINGS LTD.</b>		
<b>Prepared By</b>	<b>Sign.</b>	<b>Approved By</b>
Kiko Chan		C.H. Wong

**[www.mobicon.com](http://www.mobicon.com)**

# MIEC

## SPECIFICATION OF CRYSTAL UNIT


**PART NO. :**

**HC49S-36M2030F**

### ELECTRICAL CHARACTERISTICS

1. Nominal Frequency	36MHz
2. Holder Type	HC-49S
3. Frequency Tolerance	$\pm 30$ ppm at $25^{\circ}\text{C}$
4. Equivalent Resistance	40 Ohm max.
5. Temperature Tolerance	$\pm 30$ ppm at $-10 \sim +70^{\circ}\text{C}$
6. Aging	$\pm 5$ ppm/ year
7. Loading Capacitance	20 pF
8. Drive Level	100uW
9. Mode of Oscillation	Fundamental

### DIMENSIONS (mm)



# MIEC

## SPECIFICATION OF CRYSTAL UNIT

No.	Item	Condition of Test
1	Shock Test	Dropping from 75cm height, 3 times on firm wood Variation: Frequency drift < + 20ppm Resistance drift <+ 10 Ohm
2	Vibration Test	30 minutes in each direction 10 to 55 Hz, amplitude 0.7 ~ 0.9mm Variation: Frequency drift < $\pm$ 20ppm
3	Solderability	The dipping surface of the lead shall be at least 95% Covered with a Continuous new solder coating. Condition of test: Temperature of solder bath: 230°C $\pm$ 5°C Dipping time: 5 sec.
4	Leakage	No bubbles coming up from interior of the holder. Insulation resistance: More than 500M Ohm Condition of test: Temperature of hot water: 90°C ~ 95°C Test time: 3 min.